

# quality paints



## **TECHNICAL DATA SHEET: NEWDEN CLASSIC WUNDAKOTE MATT ACRYLIC (WHITE/PASTEL)**

### **PRODUCT DESCRIPTION:**

Newden Classic Wundakote Acrylic is a new generation water based pure matt acrylic emulsion paint that can be used on both interior and exterior surfaces. Specially formulated for those high traffic areas that require a washable and durable coating in a wide range of colours.

### **PRODUCT FEATURES:**

- Very good opacity.
- Excellent adhesion.
- Matt finish hides plaster imperfections.
- Excellent, no mess application properties.
- Fully washable.
- Low odour.
- Quick drying, two coats can be applied in one day.

### **APPLICATION AREAS:**

- Cement Plaster and Concrete
- Fibre cement
- Gypsum
- Hardboard
- Iron and Steel
- Wood

### **TECHNICAL DATA:**

<b>SPREADING AREA</b>	Although the spreading rate will vary with porosity and type of substrate, for uncoated new surfaces work on 6 - 8 SQM/l for the first coat and 7 - 9 SQM/l for subsequent coats and for when applied to sealed, previously painted substrates.
<b>VISCOSITY AT 25 °C</b>	105 - 115 KU
<b>SPECIFIC GRAVITY</b>	1,532 (approximate)
<b>SCRUBS</b>	>106,000 (approximate)
<b>SOLIDS</b>	39-41% (weight)
<b>PVC</b>	69-71%
<b>HIDING</b>	0,98-1.00
<b>DRYING TIME</b>	Touch Dry 1 hour, recoat time 2 - 4 hours (dependent on weather conditions).

### **SURFACE PREPARATION:**

- **New Surfaces:** Ensure that the surface to be painted is clean, dry and in sound condition. Fill all defects with appropriate Newden Crack Filler.
- **Cement Plaster and Concrete:** Prime with one coat Newden Plaster Primer.
- **Fibre Cement:** Prime with one coat Newden Bonding Liquid.
- **Gypsum:** Prime with one coat Newden Plaster Primer.
- **Iron and Steel:** Prime with one coat appropriate metal primer, followed by one coat of Newden Universal Undercoat.
- **Wood:** Seal knots with a knotting agent. Prime with one coat Newden Pink Primer, followed by one coat of Newden Universal Undercoat.

### **SURFACE PREPARATION (continued):**

- **Previously Painted Surfaces:** Ensure that the surface to be painted is clean, dry and free of any flaking paint.
- **Enamel in good condition:** Clean surface with Newden Sugar Soap or a mild household cleaner, rinse and allow to dry. Sand lightly, dust and clean. Prime with one coat Newden Universal Undercoat.
- **Emulsion in good condition:** Clean surface with Newden Sugar Soap or a mild household cleaner, rinse and allow to dry. Apply Newden Classic Wundakote PVA direct to the surface.
- **Surfaces in poor condition:** Strip paint completely and proceed as for new surfaces.
- **Distemper, Limewash and Chalking PVA:** Scrub down with a wire brush and sand paper until completely removed. Prime with one coat Newden Bonding Liquid or Newden Plaster Primer.

### **CLEANING:**

- **General:** Remove loose granules, flaking paint, dust, and friable and powdery material with high pressure cleaning or scrubbing with a hard bristle brush and water.
- **Fungus and Algae:** Apply household bleach liberally and work into surface. Allow 1 hour, then rinse and follow general cleaning procedures.
- **Rust:** Remove all traces of rust by abrading with medium grit sandpaper, wash and rinse the surface and allow to dry. Apply as for new Iron and Steel Surfaces.

### **PAINT APPLICATION:**

- Stir the contents thoroughly before use.
- Apply evenly with a paintbrush, roller or airless spray.
- Allow drying 2 - 4 hours before recoating, dependent on weather conditions.
- For colour consistency, ensure batch numbers on all the buckets are the same.

### **GENERAL:**

- For best results, avoid painting during inclement weather, on extremely hot surfaces and early morning or late afternoon.
- This paint is supplied ready for use, thinning is not recommended.
- Apply 2 coats of paint for best results.
- After use, clean equipment using water.

### **COLOUR RANGE AND SIZES:**

- This product can be tinted to a wide range of pastel, deep and clear shades as per the NCS catalogue.
- Available in 1, 5 and 20 litres.
- 

### **PRECAUTIONS:**

- Keep out of reach of children.
- Use in a well-ventilated area.
- Wear a suitable dust mask if sanding.
- This product is not flammable.
- It contains no toxic substances.
- Low levels of VOC (EU regulations).
- This product is lead free.

### **FIRST AID:**

- If swallowed, do not induce vomiting. Seek medical attention immediately.
- Avoid contact with eyes. If product comes in contact with eyes, rinse immediately with water and seek medical attention if irritation persists.
- If product comes in contact with skin, immediately wash contact areas with soap and water.

### **STORAGE:**

- Keep container tightly closed and store in a cool, dry, well-ventilated area away from direct sunlight, heat and severe cold.

**THE RECOMMENDATIONS CONTAINED HEREIN ARE GIVEN IN GOOD FAITH AND ARE MEANT TO GUIDE THE USER.  
WE DO NOT ACCEPT RESPONSIBILITY FOR ERROR OR OMISSION THEREIN OR DAMAGE WHICH MAY RESULT.**