

quality paints



TECHNICAL DATA SHEET: NEWDEN CONTRACTOR GENERAL PURPOSE PVA

PRODUCT DESCRIPTION:

Newden Contractor General Purpose PVA is an excellent value for money acrylic emulsion paint that can be used on both interior and exterior surfaces. After following the instructions below, apply two or more coats of Newden Contractor General Purpose PVA.

PRODUCT FEATURES:

- Very good opacity.
- Excellent adhesion and durability.
- Matt finish hides plaster imperfections.
- Excellent, no mess application properties.
- Can be wiped clean.
- Low odour.
- Quick drying, two coats can be applied in one day.
- Available in a wide range of standard colours.

APPLICATION AREAS:

- Cement Plaster and Concrete
- Fibre cement
- Gypsum
- Hardboard
- Galvanised Iron
- Iron and Steel
- Wood

TECHNICAL DATA:

SPREADING AREA	Although the spreading rate will vary with porosity and type of substrate, for uncoated new surfaces work on 6 - 8 SQM/l for the first coat and 7 - 9 SQM/l for subsequent coats and for when applied to sealed, previously painted substrates.
VISCOSITY AT 25 °C	105 - 115 KU
SPECIFIC GRAVITY	1,406 (approximate)
SCRUBS	>11000 (approximate)
SOLIDS	27-29% (weight)
PVC	78-80%
HIDING	0,96-1.00
DRYING TIME	Touch Dry 1 hour, recoat time 2 - 4 hours (dependent on weather conditions).

SURFACE PREPARATION:

- **New Surfaces:** Ensure that the surface to be painted is clean, dry and in sound condition.
- **Cement Plaster and Concrete:** Apply direct to the surface or prime with one coat Newden Fillakote. Prime any surfaces showing alkaline or chalky deposits with one coat Newden Plaster Primer.
- **Fibre Cement:** Prime with one coat Newden Bonding Liquid.
- **Gypsum:** Prime with one coat Newden Plaster Primer.
- **Iron and Steel:** Prime with one coat appropriate metal primer, followed by one coat of Universal Undercoat.
- **Wood:** Prime with one coat Newden Pink Primer, followed by one coat of Newden Universal Undercoat.
- **Previously Painted Surfaces:** Ensure that the surface to be painted is clean, dry and free of any flaking paint.

SURFACE PREPARATION (continued):

- **Enamel in good condition:** Clean surface with Newden Sugar Soap or a mild household cleaner, rinse and allow to dry. Sand lightly, dust and clean. Prime with one coat of Newden Universal Undercoat.
- **Emulsion in good condition:** Clean surface with Newden Sugar Soap or a mild household cleaner, rinse and allow to dry. Apply Newden Contractor General Purpose PVA directly to the surface.
- **Surfaces in poor condition:** Strip paint completely and proceed as for new surfaces.
- **Distemper, Limewash and Chalking PVA:** Scrub down with a wire brush and sand paper until completely removed. Prime with one coat Newden Bonding Liquid/Alkali Resistant Sealer.

CLEANING:

- **General:** Remove loose granules, flaking paint, dust, and friable and powdery material with high pressure cleaning or scrubbing with a hard bristle brush and water.
- **Fungus and Algae:** Apply household bleach liberally and work into surface. Allow 1 hour, then rinse and follow general cleaning procedures.
- **Rust:** Remove all traces of rust by abrading with medium grit sandpaper, wash and rinse the surface and allow to dry. Apply as for new Galvanised Iron and Iron and Steel Surfaces.

PAINT APPLICATION:

- Stir the contents thoroughly before use.
- Apply evenly with a paintbrush or roller.
- Allow 2 - 4 hours drying time between coats.
- This product is supplied ready for use, thinning is not recommended.
- For colour consistency, ensure that the batch numbers on all the buckets are the same.
- Do not apply in cold wet weather.

GENERAL:

- For best results, avoid painting during inclement weather, on extremely hot surfaces and early morning or late afternoon.
- After use, clean equipment using water.
- This paint can be tinted with Newden Limewash Tinter or Newden Universal Tinter.

COLOUR RANGE AND SIZES:

- This product is available in White, Desert Cream, Powder Peach, Cricket Field Green, Transkei Terracotta, Sand Dune and Karoo Brown.
- Available in 5 and 20 litres.

PRECAUTIONS:

- Keep out of reach of children.
- Use in a well-ventilated area.
- Wear a suitable dust mask if sanding.
- This product is not flammable.
- It contains no toxic substances.
- Low levels of VOC (EU regulations).
- This product is lead free.

FIRST AID:

- If swallowed, do not induce vomiting. Seek medical attention immediately.
- Avoid contact with eyes. If product comes in contact with eyes, rinse immediately with water and seek medical attention if irritation persists.
- If product comes in contact with skin, immediately wash contact areas with soap and water.

STORAGE:

- Keep container tightly closed and store in a cool, dry, well-ventilated area away from direct sunlight, heat and severe cold.

**THE RECOMMENDATIONS CONTAINED HEREIN ARE GIVEN IN GOOD FAITH AND ARE MEANT TO GUIDE THE USER.
WE DO NOT ACCEPT RESPONSIBILITY FOR ERROR OR OMISSION THEREIN OR DAMAGE WHICH MAY RESULT.**